

TECHNICAL DATA SHEET AQUATREAT 072



DESCRIPTION

- AQUATREAT 072 is a very efficient dispersant for hardness salts and metallic oxides with low phosphorous content. AQUATREAT 072 acts as corrosion inhibitor and prevents biofilm formation.
- AQUATREAT 072 has been developed to avoid and remove deposits composed of calcium carbonate, calcium sulphate, magnesium hydroxide, iron oxide, insoluble phosphates, silicates and organic deposits.
- AQUATREAT 072 contains sequestrants, anionic polymers, specific corrosion inhibitors, wetting agents and a fluorescent molecule.
- AQUATREAT 072 can be applied in closed, open and once-through cooling water systems and all other systems where abovementioned deposits may occur. AQUATREAT 072 can be used for in-service cleaning.
- AQUATREAT 072 contains 2,6% of total phosphate, excessed as PO₄.

PROPERTIES

- Appearance: Colourless/yellow liquid

- pH: 5.4 ± 1.0

Density: 1,08 ± 0,02

- Solubility in water: infinite

DOSAGE AND CONTROL

Normal dosage: 20-50 ppm on make-up water // 150-250 in cooling water. Control via tracer is possible.

Probiotic dosage (without biocides): 100 ppm on make-up // 300-500 ppm in cooling water.

Once-through system: 2-10 ppm continuously.

PACKAGING

Polyethylene drums of 22 or 220 litres, containers of 1000 litres.

HANDLING

AQUATREAT 072 is slightly irritating on skin and eyes. For more information, please read the safety data sheet.

All the given information is correct to our current knowledge. None of the indications, compositions or applications have the intention of violating existing patents. Nothing may be duplicated and/or multiplied without our written consent.

Industriezone B 122, Nieuwlandlaan 40/42
B 3200 Aarschot, Belgium
Tel. + 32 (0)16 56 21 21
aquatreat@aquatreat.be
http://www.aquatreat.eu







INTERNATIONAL AQUATREAT Co bvba

Industriezone B 122, Nieuwlandlaan 40/42
B 3200 Aarschot, Belgium
Tel. + 32 (0)16 56 21 21
aquatreat@aquatreat.be
http://www.aquatreat.eu