

TECHNICAL DATA SHEET

AQUATREAT 205

Last revision: 20.05.2020

DESCRIPTION

- AQUATREAT 205 is a very efficient dispersant for organic deposits and hardness salts.
- AQUATREAT 205 contains sequestrants and a cationic polymer.
- AQUATREAT 205 will also improve decantation and filtration and it will separate oil from water.

PROPERTIES

- Appearance: Yellow/brown liquid
- pH: 5,6 ± 1,0
- Density: 1,09 ± 0,02
- Solubility in water: infinite

DOSAGE AND CONTROL

Open recirculating cooling systems: 5-50 ppm continuously.

Filtration: 2-20 ppm on feed water.

AQUATREAT 205 is best dosed alone, as such or diluted.

PACKAGING

Polyethylene drums of 22 or 220 litres, containers of 1000 litres.

HANDLING

Wear protective gloves/clothing and eye protection. For more information, please read the safety data sheet.

All the given information is correct to our current knowledge. None of the indications, compositions or applications have the intention of violating existing patents. Nothing may be duplicated and/or multiplied without our written consent.

INTERNATIONAL AQUATREAT Co bvba

Industriezone B 122, Nieuwlandlaan 40/42 B 3200 Aarschot, Belgium Tel. + 32 (0)16 56 21 21 <u>aquatreat@aquatreat.be</u> <u>http://www.aquatreat.eu</u>