

## TECHNICAL DATA SHEET

# AQUATREAT 601

Last revision: 20.05.2020

### DESCRIPTION

- AQUATREAT 601 is a liquid product developed to prevent corrosion and deposits in high pressure boilers.
- AQUATREAT 601 contains alkaline phosphates, complying with FDA 173.310.
- AQUATREAT 601 is used to control the pH and the phosphate concentration in boiler water.

### PROPERTIES

- Appearance: Colourless liquid
- pH: > 11
- Density: 1,05 ± 0,02
- Solubility in water: infinite

### DOSAGE AND CONTROL

AQUATREAT 601 will be injected, as such or diluted, continuously into the feed tank, the feed water line or directly in the boiler (if a desuperheater is present). AQUATREAT 601 can be injected together with other treatment chemicals. AQUATREAT 601 will be dosed so that the phosphate concentration in the boiler conforms to the technical specifications of boiler water. For more information on control parameters, consult with us the European Standards.

### PACKAGING

Polyethylene drums of 22 or 220 litres, containers of 1000 litres.

### HANDLING

AQUATREAT 601 is irritating. Wear protective gloves/clothing and eye protection. In case of contact, rinse with plenty of water. For more information, please read the safety data sheet.

All the given information is correct to our current knowledge. None of the indications, compositions or applications have the intention of violating existing patents. Nothing may be duplicated and/or multiplied without our written consent.