

## TECHNICAL DATA SHEET

# AQUATREAT 605

Last revision: 20.05.2020

### DESCRIPTION

- AQUATREAT 605 is a liquid product developed to prevent corrosion and deposits in boilers until 60 bar.
- AQUATREAT 605 contains polyphosphates, dispersants and an antifoam, complying with FDA 173.310.
- AQUATREAT 605 is specially recommended for boilers operating with softened make-up water.

### PROPERTIES

- Appearance: Light yellow liquid
- pH:  $4,3 \pm 1,0$
- Density:  $1,23 \pm 0,02$
- Solubility in water: infinite

### DOSAGE AND CONTROL

AQUATREAT 605 will be injected, as such or diluted, continuously into the feed tank, the feed water line or directly in the boiler. AQUATREAT 605 can be injected together with other treatment chemicals. AQUATREAT 605 will be dosed so that the phosphate concentration in the boiler ranges between 10-30 PO<sub>4</sub>. For more information on control parameters, consult with us the European Standards.

### PACKAGING

Polyethylene drums of 22 or 220 litres, containers of 1000 litres.

### HANDLING

Wear protective gloves/clothing and eye protection. In case of contact, rinse with plenty of water. For more information, please read the safety data sheet.

All the given information is correct to our current knowledge. None of the indications, compositions or applications have the intention of violating existing patents. Nothing may be duplicated and/or multiplied without our written consent.