

TECHNICAL DATA SHEET

AQUATREAT 706

Last revision: 20.05.2020

DESCRIPTION

- AQUATREAT 706 is a liquid product based on catalysed sulphite that reacts with the dissolved oxygen in the feed water of steam boilers until 60 bar.
- AQUATREAT 706 prevents the boiler, steam and condensate lines against oxygen corrosion.
- AQUATREAT 706 complies with FDA 173.310

PROPERTIES

- Appearance: Colourless liquid
- pH: $6,7 \pm 1,0$
- Density: $1,20 \pm 0,02$
- Solubility in water: infinite

DOSAGE AND CONTROL

AQUATREAT 706 will be injected, as such or diluted, alone or together with other treatment chemicals into the feed tank, the feed water line or directly in the boiler. Avoid shaking AQUATREAT 706 drums or mixing it with other products to prevent sulphite loss due to oxidation with the air. AQUATREAT 706 will be dosed so that the excess of sulphite in the boiler water ranges between 30-60 mg/l SO_3 . For more information on control parameters, consult with us the European Standards.

PACKAGING

Polyethylene drums of 22 or 220 litres, containers of 1000 litres.

HANDLING

Wear protective gloves/clothing and eye protection. In case of contact, rinse with plenty of water. In case of contact with eyes, get medical attention. In contact with acids it liberates toxic gas. For more information, please read the safety data sheet.

All the given information is correct to our current knowledge. None of the indications, compositions or applications have the intention of violating existing patents. Nothing may be duplicated and/or multiplied without our written consent.