

TECHNICAL DATA SHEET

AQUATREAT 912

Last revision: 20.05.2020

DESCRIPTION

- AQUATREAT 912 is a high molecular weight cationic polymer based on polyimines.
- AQUATREAT 912 has been developed to be used as an emulsion breaker, flocculant, flotation aid and filtration aid.

PROPERTIES

- Appearance: Light brown liquid
- pH: 5,6 ± 1,0
- Density: 1,07 ± 0,02
- Active material: 25%

DOSAGE AND CONTROL

Emulsion breaker: 20-100 g/m³ Flocculation: 5-100 g/m³ Filtration: 5-50 g/m³

PACKAGING

Polyethylene drums of 22 or 220 litres, containers of 1000 litres.

HANDLING

AQUATREAT 912 is non-toxic. In case of contact with skin or eyes, rinse with plenty of water. For more information, please read the safety data sheet.

All the given information is correct to our current knowledge. None of the indications, compositions or applications have the intention of violating existing patents. Nothing may be duplicated and/or multiplied without our written consent.

INTERNATIONAL AQUATREAT Co bvba

Industriezone B 122, Nieuwlandlaan 40/42 B 3200 Aarschot, Belgium Tel. + 32 (0)16 56 21 21 aquatreat@aquatreat.be http://www.aquatreat.eu